CCDA 25768
1/50

FIGURE 1.0



CCDA 25,768
2/50

Figure 1.1. C8051F000 Block Diagram



CCDA 25,768
3/30

43

Figure 1.3. On-Board Clock and Reset



CODA 25,768
4/50

4
9

Figure 1.4. On-Board Memory Map



Figure 1.5. Emulation Diagram



Figure 16. Digital Crossbar Diagram



Fig 7

Figure 17. PCA Block Diagram



9008

Figure 1.8. ADC Diagram



CCDA 25,768
9/50

9

Figure ~~1.9~~. Comparator and DAC Diagram



CCDA 25,768
10/50

10

0.

Figure 5.1. ADC Functional Block Diagram



CCDA 25,768
11/50

11

Figure 5.2. ADC Track and Conversion Example Timing



CCDA 25,768
12/50

Figure 5.3. Temperature Sensor Transfer Function



CCDA 25,768
13/50

~~#~~ 13

~~Figure 5.14.~~ ADC Window Interrupt Examples, Right Justified Data



Given:
AMX0SL = 0x00, AMX0CF = 0x00, ADLJST = 0,
ADC0LTH:ADC0LTL = 0x0200,
ADC0GTH:ADC0GTL = 0x0100.

An ADC End of Conversion will cause an ADC Window Compare Interrupt (ADWINT=1) if the resulting ADC Data Word is < 0x0200 and > 0x0100.



Given:
AMX0SL = 0x00, AMX0CF = 0x00, ADLJST = 0,
ADC0LTH:ADC0LTL = 0x0100,
ADC0GTH:ADC0GTL = 0x0200.

An ADC End of Conversion will cause an ADC Window Compare Interrupt (ADWINT=1) if the resulting ADC Data Word is < 0x0100 or > 0x0200.



Given:

AMX0SL = 0x00, AMX0CF = 0x01, ADLJST = 0,
ADC0LTH:ADC0LTL = 0x0100,
ADC0GTH:ADC0GTL = 0xFFFF.

An ADC End of Conversion will cause an ADC Window Compare Interrupt (ADWINT=1) if the resulting ADC Data Word is < 0x0100 and > 0xFFFF. (Two's



Given:

AMX0SL = 0x00, AMX0CF = 0x01, ADLJST = 0,
ADC0LTH:ADC0LTH = 0xFFFF,
ADC0GTH:ADC0GTL = 0x0100.

An ADC End of Conversion will cause an ADC Window Compare Interrupt (ADWINT=1) if the resulting ADC Data Word is < 0xFFFF or > 0x0100. (Two's Complement

Figure 5.15. ADC Window Interrupt Examples, Left Justified Data



Given:
AMX0SL = 0x00, AMX0CF = 0x00, ADLJST = 1,
ADC0LTH:ADC0LTL = 0x2000,
ADC0GTH:ADC0GTL = 0x1000.

An ADC End of Conversion will cause an ADC Window Compare Interrupt (ADWINT=1) if the resulting ADC Data Word is < 0x2000 and > 0x1000.



Given:
AMX0SL = 0x00, AMX0CF = 0x00, ADLJST = 1,
ADC0LTH:ADC0LTL = 0x1000,
ADC0GTH:ADC0GTL = 0x2000.

An ADC End of Conversion will cause an ADC Window Compare Interrupt (ADWINT=1) if the resulting ADC Data Word is < 0x1000 or > 0x2000.



Given:

AMX0SL = 0x00, AMX0CF = 0x01, ADLJST = 1,
ADC0LTH:ADC0LTL = 0x1000,
ADC0GTH:ADC0GTL = 0xFFF0.

An ADC End of Conversion will cause an ADC Window Compare Interrupt (ADWINT=1) if the resulting ADC Data Word is < 0x1000 and > 0xFFF0. (Two's Complement math.)



Given:

AMX0SL = 0x00, AMX0CF = 0x01, ADLJST = 1,
ADC0LTH:ADC0LTH = 0xFFF0,
ADC0GTH:ADC0GTL = 0x1000.

An ADC End of Conversion will cause an ADC Window Compare Interrupt (ADWINT=1) if the resulting ADC Data Word is < 0xFFF0 or > 0x1000. (Two's Complement math.)

are given in Table 6.1.

15 15

Figure ~~6.1~~. DAC Functional Block Diagram



CCDA 25,768
16/50

FIG 16

Figure ~~7.1.~~ Comparator Functional Block Diagram



2017

Figure ~~7.~~2. Comparator Hysteresis Plot



CCDA 25,768
18/50

Figure 8.1. Voltage Reference Functional Block Diagram



Figure 2.1. CIP-51 Block Diagram



CCDA 25,768
20/50

Figure 22. Memory Map



CCDA 25,768

21/50

FIGURE 21

~~Figure 10.1.~~ Flash Program Memory Security Bytes



Read and Write/Erase Security Bits. (Bit 7 is MSB.)

Bit	Memory Block
7	0x7000 - 0x7DFD
6	0x6000 - 0x6FFF
5	0x5000 - 0x5FFF
4	0x4000 - 0x4FFF
3	0x3000 - 0x3FFF
2	0x2000 - 0x2FFF
1	0x1000 - 0x1FFF
0	0x0000 - 0x0FFF

FLASH Read Lock Byte

Bits7-0: Each bit locks a corresponding block of memory. (Bit 7 is MSB.)

0: Read operations are locked (disabled) for corresponding block across the JTAG interface.

1: Read operations are unlocked (enabled) for corresponding block across the JTAG interface.

FLASH Write/Erase Lock Byte

Bits7-0: Each bit locks a corresponding block of memory.

0: Write/Erase operations are locked (disabled) for corresponding block across the JTAG interface.

1: Write/Erase operations are unlocked (enabled) for corresponding block across the JTAG interface.

FLASH Access Limit Register (FLACL)

The content of this register is used as the high byte of the 16-bit software read limit address. The 16-bit read limit address value is calculated as 0xNN00 where NN is replaced by content of this register on reset. Software running at or above this address is prohibited from using the MOVX and MOVC instructions to read, write, or erase, locations below this address. Any attempts to read locations below this limit will return the value 0x00.

22

~~26~~

Figure ~~11~~.2. VDD Monitor Timing Diagram



23

Figure 12.1. Oscillator Diagram



CCDA 25,768
24/50

~~39~~ 28

Figure ~~13.2~~. Port I/O Cell Block Diagram



Figure 14.1. SMBus Block Diagram



Figure ~~14~~2. Typical SMBus Configuration



28

Figure 14.3. SMBus Transaction



CCDA 25/768
28/50

28

Figure 15.1. SPI Block Diagram



29

Figure 15.2. Typical SPI Interconnection



30

Figure 15.3. Full Duplex Operation



31

Figure 15.4. Data/Clock Timing Diagram



820

FIG 32

Figure 10.1. UART Block Diagram



Figure 16.2. UART Mode 0 Interconnect



Figure 16.3. UART Mode 0 Timing Diagram



CCDA 25,768
34/50

35 40

Figure 16.4. UART Mode 1 Timing Diagram



CCDA 25,768
35/50

36

Figure 16.5. UART Modes 1, 2, and 3 Interconnect Diagram



37

Figure ~~16~~.6. UART Modes 2 and 3 Timing Diagram



CCDA 25,768
37/60

38

Figure 16.7. UART Multi-Processor Mode Interconnect Diagram



39
44

Figure 17.1. T0 Mode 0 Block Diagram



CODA 25,768
39/50

40

Figure 17.2. T0 Mode 2 Block Diagram



41
~~40~~

Figure 17.3. T0 Mode 3 Block Diagram



42
~~49~~

Figure 17.11. T2 Mode 0 Block Diagram



43

Figure 17.12. T2 Mode 1 Block Diagram



CCDA 25,768
43/50

44

Figure 17.13. T2 Mode 2 Block Diagram



CCDA 25,768
44/50

45

Figure ~~17.19~~. Timer 3 Block Diagram



CCDA 25,768
45/50

FIGURE 46



CCDA 25,768
46/50

47

Figure ~~18.~~3. PCA Capture Mode Diagram



48

Figure ~~18.4.~~ PCA Software Timer Mode Diagram



CCDA 25,768
48/50

49
50

Figure 18.5. PCA High Speed Output Mode Diagram



Figure 18.6. PCA PWM Mode Diagram



CODA 25,768
50/50

Figure 18.7. PCA Counter/Timer Block Diagram